

PRODUCT DATA SHEET



LİNEER LED RD-2000 SERIES



LUMINARE DETAILS

HOUSING
PMMA cover
Aluminium eloxal body

VOLTAGE
24 VDC

WORKING
TEMPERATURE

COLOR TEMPERATURE

2700 K
3000 K
4000 K
5000 K
RGB

COVER TYPE

Clear CO
Opal MO

MOUNTING

Surface mounted

CONTROL SYSTEM


1-10V
DMX
DALI
ON/OFF

APPLICATIONS

Indoors
Outdoors

OPTIONAL ACCESSORIES

Power supply
Emergency Kit



3000K



4000K



5000K



RGB

IP40

IP55



RoHS



CE

| RD 2000 SERIES | | | | | |
|----------------|------------|------|------------|-------------------|--------------|
| ORDER CODE | LED/MT | LED | LUMEN/MT | POWER CONSUMPTION | IP RATE |
| RD-2100 | 24 LED/MT | 5630 | 800 LM/MT | 10 W/MT | IP 40, IP 55 |
| RD-2100 | 36 LED/MT | 5630 | 1200 LM/MT | 14 W/MT | IP 40, IP 55 |
| RD-2100 | 48 LED/MT | 5630 | 1600 LM/MT | 18 W/MT | IP 40, IP 55 |
| RD-2100 | 60 LED/MT | 5630 | 2000 LM/MT | 24 W/MT | IP 40, IP 55 |
| RD-2200 | 60 LED/MT | 3014 | 440 LM/MT | 6 W/MT | IP 40, IP 55 |
| RD-2200 | 72 LED/MT | 3014 | 520 LM/MT | 8 W/MT | IP 40, IP 55 |
| RD-2200 | 120 LED/MT | 3014 | 840 LM/MT | 12 W/MT | IP 40, IP 55 |
| RD-2200 | 160 LED/MT | 3014 | 1200 LM/MT | 16 W/MT | IP 40, IP 55 |
| RD-2700 | 36 LED/MT | 5050 | RGB | 12 W/MT | IP 40, IP 55 |
| RD-2700 | 60 LED/MT | 5050 | RGB | 18 W/MT | IP 40, IP 55 |