

PRODUCT DATA SHEET



LİNEER LED RP-3000 SERIES



LUMINARE DETAILS

HOUSING
PMMA cover
Aluminium eloxal body

VOLTAGE
24 VDC

COLOR TEMPERATURE

2700 K
3000 K
4000 K
5000 K

COVER TYPE

Opal MO

MOUNTING

PENDANT

CONTROL SYSTEM

1-10V
DALI
ON/OFF

APPLICATIONS

Indoors

OPTIONAL ACCESSORIES

Power Supply



3000K



4000K



5000K



RoHS



CE

RP-3000 SERIES						
ORDER CODE	LED/MT	LED	LUMEN/MT	POWER CONSUMPTION	COLOR TEMPERATURE	IP RATE
RP-3000.01	24 LED/MT	5630	800 LM/MT	10 W/MT	2700 3000 4000 5000	IP 40
RP-3000.02	36 LED/MT	5630	1200 LM/MT	14 W/MT	2700 3000 4000 5000	IP 40
RP-3000.03	48 LED/MT	5630	1600 LM/MT	18 W/MT	2700 3000 4000 5000	IP 40
RP-3000.04	60 LED/MT	5630	2000 LM/MT	24 W/MT	2700 3000 4000 5000	IP 40
RP-3000.05	72 LED/MT	5630	2500 LM/MT	30 W/MT	2700 3000 4000 5000	IP 40